



NOSE ASSEMBLY DATA SHEET



CAUTION:
Pintail may eject forcibly. USE DEFLECTOR TO PREVENT SEVERE PERSONAL INJURY.



WARNING:
DO NOT REMOVE - PINCH POINT

NOTES:

1. In wet applications where sealant is used: 30702 jaw assy, 46003 follower, 405717 spring & 60628 locator may be ordered for easier cleaning of sealant from jaws.
2. Nose assembly shipped with 60447 stop.
3. Yellow designates nose assemblies for lightweight GP® fasteners.

ATTACHING NOSE ASSEMBLY TO TOOL:

1. Cycle tool to ensure piston is full forward.
2. Disconnect tool from power source.
3. Remove screw and stop from tool.
4. Apply Vibra-TITE® part no. 405124 to threads on drawbar.
5. With nose assembly completely assembled, hold collet full forward in anvil and thread drawbar into piston.
6. In approximately 2-3 turns, the anvil assy threads will also engage onto tool, continue to thread drawbar and anvil completely on tool.
7. Back-off assy, no more than 1/2 turn, to position notch on anvil allowing screw and stop to be reassembled onto tool.



*Use Adapter No. 751206-1 & 731158 stroke limiter.
Optional use 731206 (No stroke limiter needed).

**Use Adapter No. 353206-1 & 745160 stroke limiter.

8/23

GAGE BILT
MADE in USA

44766 Centre Court Clinton Twp. MI 48038 USA
Ph: +1 (586) 226-1500 Fax: +1 (586) 226-1505
solutions1@gagebilt.com / www.gagebilt.com

Type:		Fasteners:		Recommended Tool:	
Non Self-Releasing 7/32" Ø		LGP® Lockbolt ASNA2391-3A ASNA2392-3A		GB206-500(A)	
				Alternate Tools: *GB731, GB731OS/206, **GB745 & GB110AOS	
Ref. No.	Qty.	Description		LGP07-300SSG	
1	1	Anvil		17016	
2	1	Collet Cartridge		27702	
3	1	Guard		60442	
4	1	Super Grip Jaw Assembly		30702-S3	
5	1	Collet Housing		20742	
6	1	Barbed Retainer		70580	
7	1	Deflector		61107	
8	1	Backguard		60519	
9	1	Drawbar		71151	
10	2	Button Head Cap Screw		408511	
11	1	Spacer		60855	