


NOSE ASSEMBLY DATA SHEET




ASSEMBLY:

Notes:

- Apply Vibra-tite® p/n 405125 to all threads and allow it to set 20 minutes prior to assembly.
 - Tighten extension (6) to piston on tool 80-100 IN-LB torque.
 - If nose assy is assembled as it is when purchased new, follow steps 3-5 to attach to tool.
- Insert super grip jaw assy (5) into rear of collet (4).
 - Thread collet (4) to extension (6) using flats provided. Insert o'ring (7) into rear of extension (6).
 - Thread assembly onto piston on tool and tighten with 9/16" wrench on collet (4) and hex key (provided with tool) into rear of piston.
 - Slide anvil & holder assembly (1) over collet (4).
 - Slide retaining nut on anvil and tighten to tool. (Note: retaining nut stop not used on this nose assy).

DISASSEMBLY:

Reverse assembly instructions.



5/07 Rev. 9/25

GAGE BILT
MADE in USA

44766 Centre Court Clinton Twp. MI 48038 USA
Ph: +1 (586) 226-1500 Fax: +1 (586) 226-1505
solutions1@gagebilt.com / www.gagebilt.com

Type:		Fasteners:	Recommended Tool: GB713	
Non Self-Releasing 3/16 & 1/4 Ø		MAGNA-GRIP® MULTI-GRIP, MAXLOK® LOCKBOLTS	Alternate Tool: GB722 & GB2480(A)	
Ref. No.	Qty.	Description	MG06-722-46	MG08-722-46
1	1	Anvil & Holder Assembly	16006	18861
2	1	Anvil	16634	18872
3	1	Holder	12258	12257
4	1	Collet	20636	20841
5	1	Super-Grip Jaw Assembly	30652-S	30860-S
6	1	Extension	70650	70650
7	1	O'Ring	400778	400778

MAGNA-GRIP® IS A REGISTERED TRADEMARK OF HOWMET AEROSPACE. MAXLOK® IS A REGISTERED TRADEMARK OF AVDEL UK LIMITED. VIBRA-TITE® IS A REGISTERED TRADEMARK OF OAKLAND CORPORATION.