



NOSE ASSEMBLY DATA SHEET



ASSEMBLY:

Notes:

- Apply Vibra-tite® p/n/ 405125 to all threads and allow it to set 20 minutes prior to assembly.
 - Tighten collet (3) and extension-collet (8) to 80 - 100 IN-LBS. (.36 - .44 Kn) torque.
 - If nose assy is assembled as it is when purchased new, follow steps 5 - 7 to attach to tool.
- Place extension-collet (8) on a flat work surface hex side up.
 - Place cap (7) on extension-collet (8). Note direction from exploded view.
 - Place spring (6) on top of cap (7). Insert follower (5) thru spring (6) and into cap (7) and extension-collet (8). Place jaw set (4) on top of follower (5).
 - Slide collet (3) over assembled parts and thread collet (3) to extension-collet (8). Snug tighten assembled parts using 9/16" wrench on collet (3) and 1/4" hex key in rear on extension-collet (8).
 - Thread assembled collet (3) and extension-collet (8) onto piston assy on tool and snug with 9/16" wrench on collet (3) and hex key into rear of piston of tool.
 - Slide anvil holder assembly (2) over assembled collet (3) and extension-collet (8).
 - Slide retaining nut from tool (retaining nut stop not used in this nose assembly) over anvil holder assembly (2) and tighten.

DISASSEMBLY:

Reverse assembly instructions.

5/06 Rev. 8/25



GAGE BILT
MADE in USA

44766 Centre Court Clinton Twp. MI 48038 USA
Ph: +1 (586) 226-1500 Fax: +1 (586) 226-1505
solutions1@gagebilt.com / www.gagebilt.com

Type:		Fastener:		Recommended Tool: GB722	
Self-Releasing		Magna-Lok®, Magna-Bulb® & Hemlok® Counter Sunk and Protruding Head Serrated Stem Structural Rivets		Alternate Tools: GB713 & GB2480(A)	
Ref. No.	Qty.	Description			MGLC06-752-23
1	1	Nose Tip (3/16")			10204-4
2	1	Anvil Holder Assembly			10942-4
3	1	Collet			20845
4	1	Jaw Set			30628
5	1	Follower			40811
6	1	Spring			50421
7	1	Cap			40810
8	1	Extension-Collet			70823