



NOSE ASSEMBLY DATA SHEET



ASSEMBLY:




Notes:

- A. Apply Vibra-tite® p/n/ 405125 to all threads and allow it to set 20 minutes prior to assembly.
- B. If nose assy is assembled as it is when purchased new, follow steps 2-4 to attach to tool.
1. Insert super grip jaw assy (3) into rear of collet (2). (Note direction in exploded view).
2. Thread assembled collet (2) onto piston of tool using flats provided and hex in rear of piston.
3. Slide anvil (1) over assembled collet (2).
4. Slide retaining nut stop and retaining nut over ears on anvil (see exploded view) and tighten to tool.

DISASSEMBLY:

Reverse assembly instructions.

SLOTS ON RETAINING NUT STOP, SUPPLIED WITH TOOL, FIT OVER EARS ON ANVIL ASSY



5/04 REV 2/24



*Anvil Assembly includes 35208 retainer.

**Blue band designates Nose Assemblies for metric GP® fasteners.

GAGE BILT
MADE in USA

44766 Centre Court Clinton Twp. MI 48038 USA
Ph: +1 (586) 226-1500 Fax: +1 (586) 226-1505
solutions1@gagebilt.com / www.gagebilt.com

Type:		Fasteners:	Recommended Tool: GB731
Non Self-Releasing 6mm Ø		Metric Groove Proportion Lockbolts	Alternate Tools: GB730 & GB2480(A)
Ref. No.	Qty.	Description	MGP6-730B-10
1	1	Anvil	16642
2	1	Collet	26655
3	1	Super-Grip Jaw Assembly	30858-S2