



NOSE ASSEMBLY DATA SHEET



CAUTION:
Pintail may eject forcibly. USE DEFLECTOR TO PREVENT SEVERE PERSONAL INJURY.



ATTACHING NOSE ASSEMBLY TO TOOL:

1. Cycle tool to ensure piston is full forward.
2. Disconnect tool from power source.
3. Remove screw and stop from tool.
4. Apply Vibra-TITE® part no. 405124 to threads on drawbar.
5. With nose assembly completely assembled, hold collet full forward in anvil and thread drawbar into piston.
6. In approximately 2-3 turns, the anvil assy threads will also engage onto tool, continue to thread drawbar and anvil completely on tool.
7. Back-off assy, no more than 1/2 turn, to position notch on anvil allowing screw and stop to be reassembled onto tool.

NOTES:

1. For dry applications where sealant is not used: 30654-S12 super grip jaw assy and 60633 spacer may be ordered.
2. Nose assembly shipped with 60447 stop.
3. Red designates nose assemblies for

7/21 REV 7/23



*Use Adapter No. 751206-1 & 731158 stroke limiter.
Optional use 731206 (No stroke limiter needed).
**Use Adapter No. 353206-1 & 745160 stroke limiter.

GAGE BILT
MADE in USA

44766 Centre Court Clinton Twp. MI 48038 USA
Ph: +1 (586) 226-1500 Fax: +1 (586) 226-1505
solutions1@gagebilt.com / www.gagebilt.com

Type:		Fasteners:	Recommended Tool: GB206-500(A)
Non Self-Releasing 5 mm Ø		MLGP® Lockbolt	Alternate Tools: *GB731, GB731OS/206, **GB745 & GB110AOS
Ref. No.	Qty.	Description	MLGP5-250S
1	1	Anvil	15042
2	1	Collet Cartridge	26630
3	1	Guard	60442
4	1	Jaw Assembly	30654
5	1	Follower	40688
6	1	Spring	405717
7	1	Locator	60628
8	1	Collet Housing	20742
9	1	Barbed Retainer	70580
10	1	Deflector	61107
11	1	Backguard	60519
12	1	Drawbar	71151
13	2	Button Head Cap Screw	408511