


NOSE ASSEMBLY DATA SHEET



APPLY LOCTITE® C5-A® ANTI-SEIZE LUBRICANT (408183) OR EQUIVALENT TO OUTSIDE OF PULLER AND INSIDE DIAMETER OF ANVIL.

ASSEMBLY:


Notes:

- Apply Vibra-tite® p/n/ 405125 to threads on anvil (1) and allow it to set 20 minutes prior to assy.
- If nose assy is assembled as it is when purchased new, follow steps 3-5 to attach to tool.

- Thread anvil (1) into anvil holder (2).
- Insert limit rod (4) with o-rings attached, into i.d. of puller (6) and push limit rod (4) thru i.d. of puller (6) until it bottoms out.
- Slide puller cap (3) over assembled puller (6) and thread puller cap (3) onto Extension-Collet (7). Thread assembled Extension-Collet (7) to piston on tool and tighten to piston on tool using flats provided.
- Slide assembled anvil (1) and anvil holder (2) over assembled puller cap (3) and assembled puller (6) on tool.
- Slide retaining nut from tool over anvil holder (2) and tighten nose assy to tool.


DISASSEMBLY:

Reverse assembly instructions.



WARNING:

EXPOSED MOVING PARTS. KEEP HANDS OFF DURING OPERATION TO PREVENT PERSONAL INJURY.



APPLY LOCTITE® C5-A® ANTI-SEIZE LUBRICANT (408183) OR EQUIVALENT TO OUTSIDE OF PULLER AS SHOWN TO KEEP FROM WEARING AGAINST ANVIL.



4/25

GAGE BILT

MADE in USA

44766 Centre Court, Clinton Twp., MI. 48038 USA

Ph: +1 (586) 226-1500 Fax: +1 (586) 226-1505

solutions1@gagebilt.com / www.gagebilt.com

Type:		Fasteners:		Recommended Tool: GB735
Self-Releasing 1/4"Ø		NeoBolt® Lockbolt		
Ref. No.	Qty.	Description		NB08-735A-60
1	1	Anvil		18030
2	1	Anvil Holder		12241-23
3	1	Puller Cap		70895
4	1	Limit Rod		70897
5	2	O-Ring		402573
6	1	Puller Assembly		30888
7	1	Extension-Collet		70822
8	1	Puller Assembly-Complete		30889

NEOBOLT® IS A REGISTERED TRADEMARK OF AVDEL UK LIMITED. LOCTITE® AND C5-A® ARE REGISTERED TRADEMARKS OF HENKEL CORPORATION U.S.A. VIBRA-TITE® IS A REGISTERED TRADEMARK OF OAKLAND CORPORATION.